



## FIST-SOSA2

### Splice only sub-assembly

Splicing sub-assemblies are the essential building blocks that allow the user to build a variety of networks.

A SOSA2 sub-assembly consists of the following parts:

- Organizer trays, designed to store fiber and splices
- A 'wraparound' grooveplate designed with slots for routing fiber to and from the organizer trays

Different types are designed to allow for:

- Single element management: fibers may be spliced according to their cable construction
- Single circuit management: The unique and essential ability to manage fibers in a single circuit fashion
- Single ribbon fiber management

## Features

- Total fiber management
  - Full fiber containment
  - Full bend radius control
  - Physical protection
- Independent of any cable construction
- Compliant with most splice types
- Loop-back facility allowing for single circuit uncut looped fiber storage on the tray.

# FIST-SOSA2

Splice only sub-assembly

## Ordering Information

### FIST - SOSA2 - X XX - X

#### Number of trays

4 or 8	For SC type tray	4	For R4/R8 type tray
2 or 4	For SE type tray	2	For R12 and MS type tray
5	For 5SE tray		

#### Type of trays

SC	For up to 4 primary or 2 secondary coated fibers
SE	For up to 12 primary or 4 secondary coated fibers
MS	For up to 24 primary or 10 secondary coated fibers
R4/8	For up to 2 ribbon 4 or 1 ribbon 8 strips
R12	For 1 ribbon 12 strip

#### Type of splice holders

A	ANT type splice holder (for SE only)
ARS	ANT + RS type splice holder (for SC only)
MS	Micro heat-shrinkable splice protector type splice holder
S	Heatshrinkable splice protector type splice holder
RS	RECORDsplice holder (not for R4/8, R12 and MS)

## Capacities

Parameter	Single Circuit Tray SC	Single Element Tray SE	Single Element Tray 5SE	Mass Storage Tray MS	Ribbon Tray R4/8	Ribbon Tray R12
Tray thickness (in UMS units) <sup>1</sup>	1	2	8/5	3	2	3
Maximum number of splices						
250 µm	4 (12) <sup>2</sup>	12 (24) <sup>3</sup>	12 (16) <sup>4</sup>	24	N/A	N/A
900 µm	2	4	N/A	10	N/A	N/A
Mixed 250/900 µm	2	4	N/A	16	N/A	N/A
Ribbon 4 mass splices	N/A	N/A	N/A	N/A	2	N/A
Ribbon 8 mass splices	N/A	N/A	N/A	N/A	1	N/A
Ribbon 12 mass splices	N/A	N/A	N/A	N/A	N/A	1
Fiber length storage (each side of splice)						
Minimum:	650 mm	650 mm	650 mm	650 mm	650 mm	650 mm
Maximum:						
250 µm	2050 mm <sup>5</sup>	2050 mm <sup>6</sup>	1500 mm	1500 mm	2050 mm <sup>7</sup>	2050 mm <sup>8</sup>
900 µm	1200 mm	1500 mm	N/A	800 mm	N/A	N/A
Mixed 250/900 µm	1500 mm	1500 mm	N/A	800 mm	N/A	N/A
Ribbon 4	N/A	N/A	N/A	N/A	2050 mm	N/A
Ribbon 8	N/A	N/A	N/A	N/A	2050 mm	N/A
Ribbon 12	N/A	N/A	N/A	N/A	N/A	2050 mm
Installed (heat-shrinkable) splice protector dimensions						
Minimum ø	2.2 mm	2.2 mm	2.2 mm	2.2 mm	3.5 mm	3.5 mm
Maximum ø	2.8 mm	2.8 mm	2.8 mm	2.8 mm	5.0 mm	5.0 mm
Minimum length	30 mm	45 mm	45 mm	45 mm	35 mm	35 mm
Maximum length	45 mm	45 mm	45 mm	45 mm	45 mm	45 mm

- The length of the FIST-SOSA2, the space of the organizer tray on the groove plate and the available space on the Fiber Arrangement System is expressed in UMS units (One UMS unit is equal to 6 mm)
- 12 splices per tray for the SC-MS tray, using micro-SMOUV
- 24 splices per tray for the SE-MS tray, using micro-SMOUV
- 16 splices per tray for the RED SMOUV / Record Splice tray
- 1500 mm for the SC-MS tray, using micro-SMOUV
- 1500 mm for the SE-MS tray, using micro-SMOUV
- Fibers are 'ribbonized'
- Fibers are 'ribbonized'

For more technical options and order quantity information, please consult the products ordering guides or your local sales representative.



[www.commscope.com](http://www.commscope.com)

Visit our website or contact your local CommScope representative for more information.

© 2016 CommScope, Inc. All rights reserved.

FIST, SMOUV, RECORDsplice and all trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services.

PS-322448-EU (02/16) (Reviewed from TC 532/DS/10 10/11)